

SCHEDA TECNICA
DATA SHEET
FICHA TÉCNICA

UR TOWER

UR4-320L

UR4-320L FAST

UR4-320L FAST & HY



*immagine a scopo illustrativo/image for illustration purposes/imagen con fines ilustrativos

FARI/LED/FOCOS

4x320W MultiLED

LUMEN/LÚMENES

180.000 lm

AREA ILLUMINATA/LIGHTING AREA
/ÁREA ILUMINADA

5000 mq/sqm/m2 (20 lux)
9300 mq/sqm/m2 (01 lux)

SPECIFICHE TECNICHE/TECHNICAL SPECIFICATIONS/DATOS DE RENDIMIENTOS

Frequenza/Rated frequency/Frecuencia	50 Hz
Voltaggio/Voltage/Voltaje	230 V
Temperatura di funzionamento/ Operating temperature /Temperatura de funcionamiento	-30/+50°
Consumi/Consumption/Consumo	
A luci tutte accese/ With lights all on /Con todas las luces encendidas	1.28 kW
Caratteristiche del palo zincato/Galvanized mast features/Características del mástil galvanizado	
Altezza/Height/Altura máxima	UR4-320L: 7m UR4-320L FAST: 7m UR4-320L FAST & HY: 8,5 m
Sistema di elevazione/ Mast /Sistema de elevación	UR4-320L: Manuale/Manual (7m) UR4-320L FAST: Manuale/Manual (7m) UR4-320L FAST & HY: Idraulico/ Hydraulic (8,5m)
Rotazione/Rotation/Rotación	350°
Resistenza aerodinamica/Wind speed resistance/Resistencia al viento	110 km/h
Telaio e Carrello/Canopy & Trailer/Chasis y remolque	
Carrello/Trailer /Remolque	UR4-320L: Carrello a traino lento/Site-tow trailer/ Remolque lento UR4-320L FAST: Carrello stradale / Road tow trailer remolque de carretera UR4-320L FAST & HY: Carrello stradale / Road tow trailer/ remolque de carretera
Gomme/ Wheels/Neumáticos	UR4-320L: 155/80R13 UR4-320L FAST: 185/70/R13 UR4-320L FAST & HY: 185/70/R13
Dimensioni per alloggio generatore/ Dimensions for generator housing/Dimensiones de la caja del generador	UR4-320L: 720x1600 mm UR4-320L FAST: 960x1950 mm UR4-320L FAST & HY: 960x1800 mm
Stabilizzatori/Stabilizers/Estabilizadores	4+1
Verniciatura/Canopy/Barnizado	Verniciatura a polvere/Powder coating paint /Recubrimiento en polvo
Optional/Opcional	
Optional inclusi su modello standard Optional included as standard Opcional incluido como estándar	Sensore di luce/Dusk to dawn sensor/Sensor de luz
Dati Spedizione/Shipment data/Datos de transporte	
Dimensioni/ Dimension/Dimensión	UR4-320L: 2130x1200x2400 mm UR4-320L FAST: 4000x1705x2450 mm UR4-320L FAST & HY: 4000x1705x2600 mm
Peso/Weight/Peso	UR4-320L: 340 kg UR4-320L FAST: 650 kg UR4-320L FAST & HY: 790 kg
Su camion/Truck/En camión	Su richiesta/On request/Bajo petición
Su Container 40"/Container 40"/En contenedor 40"	Su richiesta/On request/Bajo petición
Su Container 20"/Container 20"/En contenedor 20"	Su richiesta/On request/Bajo petición

C.G.M. Gruppi Elettrogeni srl
a socio unico

Via Decima Strada 3, 36071
Arzignano (VI) ITALY
T. +39 0444 673712 / 674152 Fax. +39 0444-675384
CF.&P.IVA 02844740247 REA 279734

info@cgmitalia.it - www.cgmitalia.it



Distributed by:

